

AR 50 - 0-15V 0-5A Regulated Power Supply

| | |
|--|------------------------|
| output voltage (V) | 0 ÷ 15 Vcc |
| output current (A) | 0 ÷ 5 Amp |
| continuous service current at max voltage(A) | 3 Amp |
| digital output meter | 3digit |
| input voltage | 230 Vca ±10%50Hz |
| operating temperature | -10C° ÷ +45C° |
| mains protection | Fuse |
| output protection | electronic |
| output stability | ±0,2V. |
| ripple | 3mV |
| main-output insulation | V=2,5V1' R >100Mohm |
| dimensions (w, h, d) | 160, 90, 255 mm |
| weight | 3,40 Kg |



The 'PROFESSIONAL' power supplies to variable voltage are the ideal combination for use in electronic workshops, plates repair in the information technology sector, teaching and servicing.

- Particularly suitable for feeding apparatuses to non-standard voltage.
- Series or common-zero connection options.
- Adjustable output voltage.
- Protection against short circuits and overloads by means of current limitation, adjustable from zero to I max.
- Display of voltage or output current on high brilliance ½ inch display unit.
- Facility for constant current operation, important when recharging storage batteries.
- Builted with discrete components and standard integrated circuits in order to facilitate servicing.
- Metal case with epoxy resin finish.