

SINGLE / THREE PHASE LOADS

3KVA - Variable with 20 steps

Resistive - Inductive - Capacitive

Mod.6020-20R
Mod.6020-20L
Mod.6020-20C

Resistive, Inductive,
Capacitive Loads.

Variable from 5% to 100%.

Provided with silk screened
front panel and with 4mm CE
safety sockets.

Robust metallic base with
rubber feet.

For R models the evacuation of
heat is obtained thanks to an
electric ventilation; a grid is
mounted to protect the fan.

Single-phase :
up to 240V 50/60Hz

Three-phase voltage:
up to 240/420V (D/Y)
50/60Hz

Power:

3kVA (Other power on
request, 0,3 to 20kVA)

Power variation:

3phase: 5% – 100%
monophase: 1,7% – 100%

Dimensions:

LxWxH: 60x45x80(h)cm.

Tabletop version

LxWxH: 70x40x40(h)cm.

English operation manual

French operation manual



MOD.6020-20R Resistive Load - Variable with 20 step

Module to realise balanced or
unbalanced 3-phase loads (star
and delta) and single-phase loads.
Each phase can be independently
varied in 20 uniform steps up to
max current value for full power.

Single-phase connection provides
60 regulation steps, from 0,32 up
to 13 Ampere

MOD.6020-20L Inductive Load - Variable 20 step

Module to realise balanced or unbalanced 3-phase loads (star and
delta) and single-phase loads. Each phase can be independently
changed in 20 uniform steps up to max current value of full load.

Single-phase connection provides 60 regulation steps.



MOD.6020-20C Capacitive Load - Variable 20 step

Module to realise balanced or unbalanced 3-phase loads (star and
delta) and single-phase loads. Each phase can be independently changed in 20 uniform
steps up to max current value of full load.

Single-phase connection provides 60 regulation steps.

Regulation steps available (3-phase):

Step	Ω	VA	Amp.	Perc.
1	1058	150	0,22	5%
2	529	300	0,43	10%
3	353	450	0,65	15%
4	265	600	0,87	20%
5	212	750	1,09	25%
6	176	900	1,30	30%
7	151	1050	1,52	35%
8	132	1200	1,74	40%
9	118	1350	1,96	45%
10	106	1500	2,17	50%
11	96,2	1650	2,39	55%
12	88,2	1800	2,61	60%
13	81,4	1950	2,83	65%
14	75,6	2100	3,04	70%
15	70,5	2250	3,26	75%
16	66,1	2400	3,48	80%
17	62,2	2550	3,70	85%
18	58,8	2700	3,91	90%
19	55,7	2850	4,13	95%
20	52,9	3000	4,35	100%

Robust sheet metal steel painted in the oven, mounted on four
robust swivel wheels for easy movement
60x45x80(h)cm.

Table-top version, dim.: 70x40x40(h)cm.

MOD.6020T-20R

